

Pneumatic Breakers



4-Bolt High Performance Models

MODEL	Standard hex chuck size (in)	Retainer type	Air inlet (in)	Length (in)	Weight (lb)	Part no.
CP 0112—30-pound class—air consumption at 90 psi: 45 cfm						
CP 0112	7/8 x 3 1/4	Latch	3/4 NPT	20	30	8900 0030 26
CP 0112 EX	7/8 x 3 1/4	Latch	3/4 NPT	20	30	8900 0030 27
CP 0112	1 x 4 1/4	Latch	3/4 NPT	20	30	8900 0030 23
CP 0112 EX	1 x 4 1/4	Latch	3/4 NPT	30 3/8	33	8900 0030 24
CP 0112 S	1 x 4 1/4	Kick Latch	3/4 NPT	20	31	8900 0030 25

CP 1210—35-pound class—air consumption at 90 psi: 48 cfm						
CP 1210	1 x 4 1/4	Latch	3/4 NPT	21 1/8	44	8900 0030 01
CP 1210S	1 x 4 1/4	Latch	3/4 NPT	21 1/8	45	8900 0030 03
CP 1210S	1 1/4 x 6	Latch	3/4 NPT	23	46	8900 0030 09
CP 1210S	1 1/8 x 6	Latch	3/4 NPT	23	46	8900 0030 07
CP 1210 SVR	1 x 4 1/4	Latch	3/4 NPT	23 1/2	51	8900 0030 05
CP 1210 SVR	1 1/8 x 6	Latch	3/4 NPT	25 1/2	55	8900 0030 08
CP 1210 SVR	1 1/4 x 6	Latch	3/4 NPT	25 1/2	55	8900 0030 10

CP 1260—60-pound class—air consumption at 90 psi: 63 cfm						
CP 1260	1 1/8 x 6	Latch	3/4 NPT	27	64	8900 0030 29
CP 1260 S	1 1/8 x 6	Latch	3/4 NPT	27	65	8900 0030 31
CP 1260 SVR	1 1/8 x 6	Latch	3/4 NPT	29	75	8900 0030 33
CP 1260	1 1/4 x 6	Latch	3/4 NPT	27	64	8900 0030 28
CP 1260 S	1 1/4 x 6	Latch	3/4 NPT	27	65	8900 0030 30
CP 1260 SVR	1 1/4 x 6	Latch	3/4 NPT	29	75	8900 0030 32

CP 1290—90-pound class—air consumption at 90 psi: 81 cfm						
CP 1290	1 1/8 x 6	Latch	3/4 NPT	29	82	8900 0030 38
CP 1290 S	1 1/8 x 6	Latch	3/4 NPT	29	83	8900 0030 40
CP 1290 SVR	1 1/8 x 6	Latch	3/4 NPT	31	96	8900 0030 42
CP 1290	1 1/4 x 6	Latch	3/4 NPT	29	82	8900 0030 37
CP 1290 S	1 1/4 x 6	Latch	3/4 NPT	29	83	8900 0030 39
CP 1290 SVR	1 1/4 x 6	Latch	3/4 NPT	31	96	8900 0030 41

EX = Extended handle for trench work; S = Silenced models; SVR = Silenced & Vibration Reduced models
Spike Drivers also available, CP 1260 S SPDR 8900 0030 34, CP 1269 S SPDR 8900 0030 43
Note: CP 1230 / CP 1240 replaced by CP 1260 / CP 1290

CP four-bolt breakers require minimal servicing to maintain peak operating efficiency over extended periods of rugged use.

Durable polyurethane front-head springs, side bolts and anvil minimize repairs.

CP breakers can be ordered with mufflers, or mufflers can be purchased separately.

Retrofit dust suppression spray kits
see page 21



Standard model
CP 0112



Standard model
CP 1210, 1260 and 1290



CP1210S

CP 0112 and CP 1210

The CP 0112 (30-pound class) and CP 1210 (35-pound class) demolition tools are lightweight yet rugged. They're designed for light to medium construction and plant maintenance work such as demolition of floors, pavement, bridge maintenance, asphalt, frozen ground and masonry walls. They're very popular for bridge deck jobs. CP 0112 EX has an extended handle for trench work.

- Alloy steel forgings provide excellent durability
- Four-bolt backhead design withstands rugged use
- CP 0112 is equipped with an integral oiler that provides continuous lubrication
- Heavy-duty front headsprings on CP 1210 reduce reaction back to operator
- CP 1210S is equipped with a silencer to reduce sound level
- Vibration reduced handle (SVR) is available on the CP 1210 SVR

CP 1260 and CP 1290

The CP 1260 (60-pound class) and CP 1290 (90-pound class) demolition tools are engineered to deliver the power and durability necessary for a variety of construction and plant maintenance applications such as breaking heavy and reinforced concrete, frozen ground, asphalt, boulders and pavement.

- Alloy steel forgings provide excellent durability
- Four-bolt backhead design withstands rugged use
- Integral oiler provides continuous lubrication
- Durable polyurethane front headsprings reduce reaction back to operator
- Reversible piston reduces maintenance cost
- Air inlet swivel for easy maneuverability
- CP 1260 S and CP 1290 S are equipped with silencers
- Vibration reduced handle (SVR) available on the CP 1260 SVR and CP 1290 SVR



Breakers can be ordered with mufflers or mufflers can be purchased separately. Refer to page 5 for part numbers.



Vibration reduced models (VRS) are also silenced.
1210 SVR
1260 SVR
1290 SVR