

# ZS4000

## Zero-Turn, Stand-On Mower



Stability. Agility. Profitability. With a compact size, extra ground clearance and large drive tires, the ZS4000 gets over and around obstacles and on to the next job.

- Vibration-dampening platform technology
- Hydrostatic transmission delivers powerful torque, smooth power output
- Easy access maintenance
- Fuel capacity up to 6.5 gallons
- Featuring the [AirFX™ Cutting Deck](#)

### Starting at

**\$9,699 USD\*\* or finance \$162/month USD\***

### Special Offers

**As low as 0% for 60 months\* or rebates up to \$1,000 USD\* / \$1,350 CAD\* in lieu of financing on Bobcat ZS4000 zero turn stand-on mowers. Offers end June 30, 2025.**

[Search Inventory](#)[Contact Dealer](#)[View Offers](#)[Find Dealer](#)[Download Brochure](#)

## ZS4000 Overview

Get stand-up performance with the ZS4000 zero-turn stand-on mower. The ZS4000 is equipped with commercial-grade features including the bullnose AirFX™ cutting system, a low center of gravity and tool-free controls – all designed to let you maneuver through tough obstacles with total confidence. Equipped with a powerful Kawasaki® FX series engine, this zero-turn mower also boasts a heavy-duty drive system for quick ground speeds.

- Featuring Air-Gap baffles and vacuum seals, the ZS4000's AirFX cutting deck increases lift on every blade of grass for unmatched precision. A 36-inch DuraDeck™ cutting system is also available.
- Command unmatched control and response from ergonomic, tool-free controls with adjustable tracking that put a whole new level of zero-turn, stand-on mowing control right at your fingertips.
- When it comes to maneuvering around obstacles or tight spaces, the ZS4000 has an intuitive operator-station design that provides a superior “center of mass” stability that makes you feel like you’re one with the machine.

## ZS4000 Specs & Compare

▲ ZS4000 Key Specifications			
ZS4036SJ	ZS4052SK	ZS4061SK	ZS4048SF
Engine Model			
Kaw FX600V	Kaw FT730 EFI	Kaw FT730 EFI	Kaw FX651V
Displacement			
603 cubic cm	726 cubic cm	726 cubic cm	726 cubic cm
Transmission Type			
HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
Pump Displacement			
10 cubic cm	12 cubic cm	12 cubic cm	12 cubic cm
Cutting Height Range			
1.5–4.5	1.5–4.5	1.5–4.5	1.5–4.5
Mower Deck			

DuraDeck Cutting System	AirFX™ Cutting System	AirFX™ Cutting System	AirFX™ Cutting System
<b>Width</b>			
36 in	52 in	61 in	48 in
<b>^ Engine</b>			
<b>ZS4036SJ</b>	<b>ZS4052SK</b>	<b>ZS4061SK</b>	<b>ZS4048SF</b>
<b>Engine Model</b>			
Kaw FX600V	Kaw FT730 EFI	Kaw FT730 EFI	Kaw FX651V
<b>Fuel Tank</b>			
5.1 gal	6.5 gal	6.5 gal	6.5 gal
<b>Horsepower</b>			
19 hp	26 hp	26 hp	20.5 hp
<b>Displacement</b>			
603 cubic cm	726 cubic cm	726 cubic cm	726 cubic cm
<b>^ Performance</b>			
<b>ZS4036SJ</b>	<b>ZS4052SK</b>	<b>ZS4061SK</b>	<b>ZS4048SF</b>
<b>Machine Weight - Wet</b>			
800 lbs	991 lbs	1028 lbs	961 lbs
<b>^ Power/Electrical</b>			
<b>ZS4036SJ</b>	<b>ZS4052SK</b>	<b>ZS4061SK</b>	<b>ZS4048SF</b>
<b>Charging System</b>			
15 amp	15 amp	15 amp	15 amp
<b>^ Transmission</b>			
<b>ZS4036SJ</b>	<b>ZS4052SK</b>	<b>ZS4061SK</b>	<b>ZS4048SF</b>
<b>Transmission Type</b>			
HG ZT-3100 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles	HG ZT-3400 Hydrostatic Transaxles
<b>Pump Displacement</b>			
10 cubic cm	12 cubic cm	12 cubic cm	12 cubic cm
<b>Oil Capacity</b>			
4 qt	4 qt	4 qt	4 qt
<b>Travel Speed</b>			
9 mph	10.5 mph	10.5 mph	10.5 mph
<b>Travel Speed - Reverse</b>			
3.5 mph	3.5 mph	3.5 mph	3.5 mph
<b>^ Mower Seat</b>			
<b>ZS4036SJ</b>	<b>ZS4052SK</b>	<b>ZS4061SK</b>	<b>ZS4048SF</b>

Fore-Aft Adjustment			
Flip Up and Latch	Flip Up and Latch	Flip Up and Latch	Flip Up and Latch
Description			
Operator Pad - tethered, removable	Operator Pad - tethered, removable	Operator Pad - tethered, removable	Operator Pad - tethered, removable

Wheels			
ZS4036SJ	ZS4052SK	ZS4061SK	ZS4048SF
Front Caster Wheel Size			
11 x 6.0-5	13 x 6.5-6	13 x 6.5-6	13 x 6.5-6
Caster Arm			
Bolt-On	Bolt-On	Bolt-On	Bolt-On
Drive Wheel Size			
20 x 8.0-10	23 x 10.5-12	23 x 10.5-12	23 x 8.5-12

Frame			
ZS4036SJ	ZS4052SK	ZS4061SK	ZS4048SF
Front and Rear			
Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing	Welded 7-gauge Steel; 1.5 x 2.5 in Steel Tubing
Length			
64 in	64 in	64 in	64 in

Deck			
ZS4036SJ	ZS4052SK	ZS4061SK	ZS4048SF
Cutting Height Range			
1.5-4.5	1.5-4.5	1.5-4.5	1.5-4.5
Mower Deck			
DuraDeck Cutting System	AirFX™ Cutting System	AirFX™ Cutting System	AirFX™ Cutting System
Discharge Chute			
Flexible Molded Polymer	Flexible Molded Polymer	Flexible Molded Polymer	Flexible Molded Polymer
Mower Blade Tip Speed			
17600 ft/min	18586 ft/min	18500 ft/min	17800 ft/min
Width			
36 in	52 in	61 in	48 in

## ZS4000 Features & Benefits

Expand all ▾

▾ Performance <sup>3</sup>

▾ Comfort <sup>1</sup>

▾ Versatility <sup>2</sup>

▾ Serviceability <sup>1</sup>

▾ Durability <sup>1</sup>

\*Offer ends 6/30/2025. Available at participating and eligible dealers only. Offer may vary by product type, series, model and select units in dealer's current inventory. Must take delivery from dealer stock by 6/30/2025. Offers available on new equipment in US and Canada only. Some restrictions apply. Length of contract and rate may vary. Monthly payment subject to change. Prior purchases not eligible. See dealer for details. Financing provided on approval of credit by authorized Bobcat finance providers to well-qualified buyers. All finance programs and rates are subject to final approval by the applicable Bobcat finance provider and are subject to change at any time without notice. Administrative fees may apply. Offer not available to government accounts, national accounts and municipal/utility bid customers. Bobcat Company reserves the right to extend or discontinue any of these programs at any time without prior notice.

\*\*Suggested List Price is the manufacturer's suggested pricing for base models. It does not include freight, pre-delivery inspection, tax, options, accessories, or attachments. Only for products sold in the U.S. Final sale price is determined independently by the local dealer. Product configuration may differ from image(s) provided. See dealer for full product details. Bobcat Company reserves the right to change suggested resale prices, product specifications, and options at any time.



**WARNING:** This product can expose you to chemicals including engine exhaust (including diesel engine exhaust when equipped), lead and lead compounds, mineral oils, soots, phthalates, and carbon monoxide which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

*Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.*